



Specializing in Research & Development of High Performance Pressure Sensitive Tapes

Product Data Sheet

SC-1060

Product Description: Striped safety warning duct tape. Polyethylene coated cloth with natural rubber adhesive system used for permanent and temporary marking of hazardous areas, wires, cords, aisles, etc. Product is hand tearable and user friendly. Does remove cleanly from most surfaces.

Physical Characteristics

Nominal Values

Total Tape Thickness	11.0 mils
Backing Type	Polyethylene Coated Cloth
Tensile Strength	20 lbs/in
Temperature Range	32F to 150F
180 Degree Peel Adhesion to Stainless Steel	59 oz/in
Color	Black/Yellow diagonal stripes
COO	Korea

Tape Application

To achieve ultimate bond strength please be sure materials being bonded are clean and free of dust, dirt, oil or other substances which can effect the bond of the tape adhesive. Firm application pressure will promote a strong, long lasting bond. Adhesive bond strength is dependent upon the material type being bonded. If a variety of materials are being used, please be sure to test the suitability of product performance with each material. Please contact Custom Adhesive Products at the phone number below with questions regarding your taping applications and needs.

Notice: Physical and performance values list above are average values obtained from tests performed according to PSTC or ASTM standard test methods. Custom Adhesive Products does not make any warrant of any kind as to the results listed above. The information listed above does not represent a performance guarantee. Product performance may vary with each individual application and the purchaser should test the product prior to use and satisfy themselves regarding product functionality in their application. Custom Adhesive Products shall not be liable for damages in excess of the purchase price of its products or for incidental or consequential damages.