



Specializing in Research & Development of High Performance Pressure Sensitive Tapes

Product Data Sheet SC-1490

Product Description: Product SC-1490 tape is transparent, biodegradable and hand tear-able. Static free for use in the electronics industry. Ideal for sealing or mending in the office, school, home, and industrial applications. Use where biodegradable tape is required.

Physical Characteristics	Nominal Values
Markets	Flexible Packaging
Total Tape Thickness	1.8 mils
Backing Material	Pure Cellulose
Carrier Thickness	1.1 mils
Adhesives Type	Solvent Based Natural Rubber
180° Peel Adhesion to Stainless Steel	30 oz./in.
Heat Resistance	Low
Color	Colorless

Tape Application: To achieve ultimate bond strength please be sure materials being bonded are clean and free of dust, dirt, oil or other substances which can affect the bond of the tape adhesive. Firm application pressure will promote a strong, long-lasting bond. Adhesive bond strength is dependent upon the material type being bonded. If a variety of materials are being used, please be sure to test the suitability of product performance with each material. Please contact Custom Adhesive Products at the phone number below with questions regarding your taping applications and needs.

Notice: Physical and performance values listed above are average values obtained from tests performed according to PSTC or ASTM standard test methods. Custom Adhesive Products does not make any warrant of any kind as to the results listed above. The information listed above does not represent a performance guarantee. Product performance may vary with each individual application and the purchaser should test the product prior to use and satisfy themselves regarding product functionality in their application. Custom Adhesive Products shall not be liable for damages more than the purchase price of its products or for incidental or consequential damages.

