Specializing in Research & Development of High Performance Pressure Sensitive Tapes

Product Data Sheet
SC-2107

Product Description: SC-2107 is backed with PET film and reinforced with glass fiber.

Physical Characteristics	Nominal Values
Applications	Core-Starting, End-Tabbing
Total Tape Thickness	5.5 mils
Backing Material	PET
Adhesives Type	Synthetic Rubber
180º Peel Adhesion to Stainless Steel	79 oz./in.
Heat Resistance	Low
Color	Milk White

Tape Application: To achieve ultimate bond strength please be sure materials being bonded are clean and free of dust, dirt, oil or other substances which can affect the bond of the tape adhesive. Firm application pressure will promote a strong, long-lasting bond. Adhesive bond strength is dependent upon the material type being bonded. If a variety of materials are being used, please be sure to test the suitability of product performance with each material. Please contact Custom Adhesive Products at the phone number below with questions regarding your taping applications and needs.

Notice: Physical and performance values listed above are average values obtained from tests performed according to PSTC or ASTM standard test methods. Custom Adhesive Products does not make any warrant of any kind as to the results listed above. The information listed above does not represent a performance guarantee. Product performance may vary with each individual application and the purchaser should test the product prior to use and satisfy themselves regarding product functionality in their application. Custom Adhesive Products shall not be liable for damages more than the purchase price of its products or for incidental or consequential damages.

WWW.CAPTAPE.COM • 2909 WOLFF ST. RACINE, WI 53404
(PH) 262-595-0568 • (FAX) 262-595-0566