



Specializing in Research & Development of High Performance Pressure Sensitive Tapes

Product Data Sheet

SC-9000

Product Description: 15 mil friction tape made with black cotton cloth with a non-corrosive rubber resin adhesive. Product is hand-tearable and conformable. Resistant to humidity and galvanic corrosion. Used for insulation and to protect industrial harnesses and electrical wires from physical damage caused by friction, for over wrapping low voltage splices and general electrical maintenance jobs. Standard length is 60 feet.

Physical Characteristics	Nominal Values
Tape Thickness	15 mils
Tensile Strength	42 lbs/in
Elongation	8 %
Dielectric Strength	1000V
Insulation Class	176F
Colors Available	Black

Tape Application: To achieve ultimate bond strength please be sure materials being bonded are clean and free of dust, dirt, oil or other substances which can affect the bond of the tape adhesive. Firm application pressure will promote a strong, long lasting bond. Adhesive bond strength is dependent upon the material type being bonded. If a variety of materials are being used, please be sure to test the suitability of product performance with each material. Please contact Custom Adhesive Products at the phone number below with questions regarding your taping applications and needs.

Notice: Physical and performance values listed above are average values obtained from tests performed according to PSTC or ASTM standard test methods. Custom Adhesive Products does not make any warrant of any kind as to the results listed above. The information listed above does not represent a performance guarantee. Product performance may vary with each individual application and the purchaser should test the product prior to use and satisfy themselves regarding product functionality in their application. Custom Adhesive Products shall not be liable for damages in excess of the purchase price of its products or for incidental or consequential damages.